

NEW METHOD TO TEST AIRTIGHTNESS OF NEARLY ZERO ENERGY DWELLINGS


Wouter Borsboom, TNO
Timothy Lanooy, ACIN
Wim Kornaat, TNO
Willem de Gids, VentGuide

TNO innovation
for life

AIVC Workshop BRANZ, Wellington 2018

WOUTER BORSBOOM, TNO

Business consultant, energy built environment.






Example nearly zero energy dwelling: $R_c=5-6$, N_{50} ach 0.8, heat recovery, heat pump, PV -> can be built without subsidies

WHAT SHOULD A HEALTHY ENERGY EFFICIENT DWELLING OFFER?

- › A dwelling with sufficient ventilation
- › A cool house in the summer
- › A dwelling with less exposure to conterminants






GOOD PERFORMANCE OF VENTILATION NEEDS AIRTIGHT DWELLINGS

- › Airtightness at least $N50 < 4$
- › High performance dwelling are mostly airtight **$N50 < 1$** to:
 - **Reduce the installed capacity** heating / cooling
 - **Reduce energy demand** Heating & Cooling


Darling, you told me that you stopped smoking..



PROBLEMS IN QUALITY CONTROL

- › Specified airtightness is not met in many cases
- › **Effects:**
 - **Roomset points is not met** through insufficient capacity
 - **Thermal comfort**
 - temperature control
 - draught
 - **Reduced indoor air quality** trough advantitious ventilation
 - **Increased energy bill** through extra heating and cooling demand
 - Example renovation: **design ach 3, but realized ach 15**

Top 3 air-leakages in 13 nearly zero energy dwellings



NEED FOR 100% QUALITY CHECKS AIRTIGHTNESS

- › Both new and retrofitted dwellings
- › Meet European Carbon reduction targets
- › Last week in the Netherlands **statement** “healthy living without gas heating” by the **building industry**, 21 companies and associations to perform a **100% check of airtightness** and ventilation and **N50 < ach 1,5**



QUICK & SIMPLE AIRTIGHTNESS TEST

Reason of the research:


The association of manufacturers of ventilation systems and installers joint forces: The challenge is to make **an airtightness test method suitable for all kind of craftsmen and inspectors.**





UNETO-VNI



**Common
Air Leakage
Paths in
Houses**




PRINCIPLE OF THE TEST




EXAMPLE TEST SIGNAL

› Measurement signal



› Corrected signal



PRACTICAL ISSUES

- › Mechanical exhaust or supply, natural inlet or range hood
 - Closed grills

or

- › Balanced ventilation with heat recovery
 - Switch off the supply or exhaust and block it

SCOPE OF THE METHODOLOGY

- › Required airtightness **N50 < 4**
- › Sufficient **mechanical flow > 20 l/s** to have a pressure of > 10 Pa
 - **Whole house ventilation** (20-70 l/s)
 - Or a **range hood**

Every country has it's own rules how the measurements take place.
For instance how to handle fire place, open gas boilers etc.

LABORATORY CALIBRATIONS

| Calibrated opening | q_v , blower door (l/s) | n (-) | $q_{v,system}$ (l/s) | $q_{v,new}$ (l/s) | $q_{v,new}$ (l/s) | Δq_v (l/s) | Δq_v (%) |
|--------------------|---------------------------|---------|----------------------|-------------------|-------------------|--------------------|------------------|
| | | | ± 1.0 l/s | n measured | $n = 0.66$ | | |
| Closed | 17.0 | 0.68 | 49.0 | 18.6 ± 0.5 | 19.1 ± 2.8 | 1.6 | 9.4 |
| | 16.1 | 0.70 | 48.5 | 17.6 ± 0.4 | 18.9 ± 2.8 | 1.5 | 9.3 |
| 12.5 | 30.5 | 0.62 | 48.5 | 30.7 ± 1.3 | 29.8 ± 2.6 | 0.2 | 0.7 |
| | 34.6 | 0.58 | 48.5 | 32.4 ± 1.6 | 30.8 ± 2.7 | -2.2 | -6.4 |
| 25 | 44.7 | 0.58 | 48.5 | 47.5 ± 1.5 | 47.3 ± 1.8 | 2.8 | 6.3 |
| | 51.7 | 0.53 | 48.5 | 42.9 ± 9.3 | 41.7 ± 11.4 | -8.8 | -17.0 |
| 50 | 86.7 | 0.53 | 48.5 | 77.7 ± 10.1 | 86.0 ± 16.0 | -9.0 | -10.4 |
| | 77.7 | 0.52 | 48.5 | 66.6 ± 26.5 | 72.5 ± 38.5 | -11.1 | -14.3 |
| 75 | 77.7 | 0.52 | 65.0 | 72.8 ± 3.4 | 74.9 ± 4.6 | -4.9 | -6.3 |
| | 77.7 | 0.52 | 104.0 | 79.3 ± 2.6 | 73.7 ± 4.9 | 1.6 | 2.1 |
| | 101.7 | 0.51 | 49.0 | 82.5 ± 18.6 | 96.2 ± 30.2 | -19.2 | -18.9 |
| | 101.2 | 0.51 | 65.5 | 97.9 ± 15.1 | 110.1 ± 23.8 | -3.3 | -3.3 |
| | 101.2 | 0.51 | 104.5 | 106.9 ± 6.7 | 107.6 ± 8.7 | 5.7 | 5.6 |
| | 101.2 | 0.51 | 104.5 | 101.5 ± 6.9 | 100.6 ± 8.9 | 0.3 | 0.3 |

fixed and assumed n

LABORATORY CALIBRATIONS

| Calibrated opening | q_v , blower door (l/s) | n (-) | $q_{v,system}$ (l/s) | $q_{v,new}$ (l/s) | $q_{v,new}$ (l/s) | Δq_v (l/s) | Δq_v (%) |
|--------------------|---------------------------|---------|----------------------|-------------------|-------------------|--------------------|------------------|
| | | | ± 1.0 l/s | n measured | $n = 0.66$ | | |
| Closed | 17.0 | 0.68 | 49.0 | 18.6 ± 0.5 | 19.1 ± 2.8 | 1.6 | 9.4 |
| | 16.1 | 0.70 | 48.5 | 17.6 ± 0.4 | 18.9 ± 2.8 | 1.5 | 9.3 |
| 12.5 | 30.5 | 0.62 | 48.5 | 30.7 ± 1.3 | 29.8 ± 2.6 | 0.2 | 0.7 |
| | 34.6 | 0.58 | 48.5 | 32.4 ± 1.6 | 30.8 ± 2.7 | -2.2 | -6.4 |
| 25 | 44.7 | 0.58 | 48.5 | 47.5 ± 1.5 | 47.3 ± 1.8 | 2.8 | 6.3 |
| | 51.7 | 0.53 | 48.5 | 42.9 ± 9.3 | 41.7 ± 11.4 | -8.8 | -17.0 |
| 50 | 86.7 | 0.53 | 48.5 | 77.7 ± 10.1 | 86.0 ± 16.0 | -9.0 | -10.4 |
| | 77.7 | 0.52 | 48.5 | 66.6 ± 26.5 | 72.5 ± 38.5 | -11.1 | -14.3 |
| | 77.7 | 0.52 | 65.0 | 72.8 ± 3.4 | 74.9 ± 4.6 | -4.9 | -6.3 |
| 75 | 77.7 | 0.52 | 104.0 | 79.3 ± 2.6 | 73.7 ± 4.9 | 1.6 | 2.1 |
| | 101.7 | 0.51 | 49.0 | 82.5 ± 18.6 | 96.2 ± 30.2 | -19.2 | -18.9 |
| | 101.2 | 0.51 | 65.5 | 97.9 ± 15.1 | 110.1 ± 23.8 | -3.3 | -3.3 |
| | 101.2 | 0.51 | 104.5 | 106.9 ± 6.7 | 107.6 ± 8.7 | 5.7 | 5.6 |
| | 101.2 | 0.51 | 104.5 | 101.5 ± 6.9 | 100.6 ± 8.9 | 0.3 | 0.3 |

fixed and assumed n

LABORATORY CALIBRATIONS

| Calibrated opening | $q_{v, \text{blower door}}$ (l/s) | n (-) | $q_{v, \text{system}}$ (l/s) | $q_{v, \text{new}}$ (l/s) | $q_{v, \text{new}}$ (l/s) | Δq_v (l/s) | Δq_v (%) |
|--------------------|-----------------------------------|---------|------------------------------|---------------------------|---------------------------|--------------------|------------------|
| | | | ± 1.0 l/s | n measured | $n = 0.66$ | | |
| Closed | 17.0 | 0.68 | 49.0 | 18.6 ± 0.5 | 19.1 ± 2.8 | 1.6 | 9.4 |
| | 16.1 | 0.70 | 48.5 | 17.6 ± 0.4 | 18.9 ± 2.8 | 1.5 | 9.3 |
| 12.5 | 30.5 | 0.62 | 48.5 | 30.7 ± 1.3 | 29.8 ± 2.6 | 0.2 | 0.7 |
| | 34.6 | 0.58 | 48.5 | 32.4 ± 1.6 | 30.8 ± 2.7 | -2.2 | -6.4 |
| 25 | 44.7 | 0.58 | 48.5 | 47.5 ± 1.5 | 47.3 ± 1.8 | 2.8 | 6.3 |
| | 51.7 | 0.53 | 48.5 | 42.9 ± 9.3 | 41.7 ± 11.4 | -8.8 | -17.0 |
| 50 | 86.7 | 0.53 | 48.5 | 77.7 ± 10.1 | 86.0 ± 16.0 | -9.0 | -10.4 |
| | 77.7 | 0.52 | 48.5 | 66.6 ± 26.5 | 72.5 ± 38.5 | -11.1 | -14.3 |
| | 77.7 | 0.52 | 65.0 | 72.8 ± 3.4 | 74.9 ± 4.6 | -4.9 | -6.3 |
| 75 | 77.7 | 0.52 | 104.0 | 79.3 ± 2.6 | 73.7 ± 4.9 | 1.6 | 2.1 |
| | 101.7 | 0.51 | 49.0 | 82.5 ± 18.6 | 96.2 ± 30.2 | -19.2 | -18.9 |
| | 101.2 | 0.51 | 65.5 | 97.9 ± 15.1 | 110.1 ± 23.8 | -3.3 | -3.3 |
| | 101.2 | 0.51 | 104.5 | 106.9 ± 6.7 | 107.6 ± 8.7 | 5.7 | 5.6 |
| | 101.2 | 0.51 | 104.5 | 101.5 ± 6.9 | 100.6 ± 8.9 | 0.3 | 0.3 |

fixed and assumed n

LABORATORY CALIBRATIONS


| Calibrated opening | $q_{v, \text{blower door}}$ (l/s) | n (-) | $q_{v, \text{system}}$ (l/s) | $q_{v, \text{new}}$ (l/s) | $q_{v, \text{new}}$ (l/s) | Δq_v (l/s) | Δq_v (%) |
|--------------------|-----------------------------------|---------|------------------------------|---------------------------|---------------------------|--------------------|------------------|
| | | | ± 1.0 l/s | n measured | $n = 0.66$ | | |
| Closed | 17.0 | 0.68 | 49.0 | 18.6 \pm 0.5 | 19.1 \pm 2.8 | 1.6 | 9.4 |
| | 16.1 | 0.70 | 48.5 | 17.6 \pm 0.4 | 18.9 \pm 2.8 | 1.5 | 9.3 |
| 12.5 | 30.5 | 0.62 | 48.5 | 30.7 \pm 1.3 | 29.8 \pm 2.6 | 0.2 | 0.7 |
| | 34.6 | 0.58 | 48.5 | 32.4 \pm 1.6 | 30.8 \pm 2.7 | -2.2 | -6.4 |
| 25 | 44.7 | 0.58 | 48.5 | 47.5 \pm 1.5 | 47.3 \pm 1.8 | 2.8 | 6.3 |
| | 51.7 | 0.53 | 48.5 | 42.9 \pm 9.3 | 41.7 \pm 11.4 | -8.8 | -17.0 |
| 50 | 86.7 | 0.53 | 48.5 | 77.7 \pm 10.1 | 86.0 \pm 16.0 | -9.0 | -10.4 |
| | 77.7 | 0.52 | 48.5 | 66.6 \pm 26.5 | 72.5 \pm 38.5 | -11.1 | -14.3 |
| | 77.7 | 0.52 | 65.0 | 72.8 \pm 3.4 | 74.9 \pm 4.6 | -4.9 | -6.3 |
| | 77.7 | 0.52 | 104.0 | 79.3 \pm 2.6 | 73.7 \pm 4.9 | 1.6 | 2.1 |
| 75 | 101.7 | 0.51 | 49.0 | 82.5 \pm 18.6 | 96.2 \pm 30.2 | -19.2 | -18.9 |
| | 101.2 | 0.51 | 65.5 | 97.9 \pm 15.1 | 110.1 \pm 23.8 | -3.3 | -3.3 |
| | 101.2 | 0.51 | 104.5 | 106.9 \pm 6.7 | 107.6 \pm 8.7 | 5.7 | 5.6 |
| | 101.2 | 0.51 | 104.5 | 101.5 \pm 6.9 | 100.6 \pm 8.9 | 0.3 | 0.3 |

fixed and assumed n


FIELD MEASUREMENTS




n50 (ach) blowerdoor versus new method per dwelling



n50 (ach) blowerdoor versus new method per dwelling



MEASURING AT HIGH WIND SPEED



$q_{v,10}$ new = 34.2 l/s
(N50=1,1)

Blowerdoor fan off 40 Pa

$q_{v,10}$ blower = 31.6 l/s at
another day

RESULTS FIELD STUDIES

- › **Flow was more difficult to measured** in the **field** studies due to summing up of flow of different outlets. A fault in the flow has a strong impact in overall accuracy
- › Room for improvement to **calculate pressure difference**
- › Average **difference** between blower door and new test methode up about 10%, max 20%

DISCUSSION

› Advantages

- **Quick**, about 20 minutes
- **Compact** can be placed in a bag pack
- **Simple**
- **Inaccuracy < 20%**

› Disadvantages

- **Flow coefficient needs multiple** measurements with different flows
- **Less visual impression smoke test** in cases with lower pressure
- When ventilation flow is not measured by the ventilation unit, **multiple measurements of flows through valves leading to lower accuracy**



› **THANKS FOR YOUR ATTENTION**

Contact:
Wouter Borsboom
wouter.borsboom@tno.nl

TNO innovation
for life