I.

A SITE STUDY OF SOIL CHARACTERISTICS AND SOIL GAS RADON

by: Richard Lively, Minnesota Geological Survey, 2642 University Ave. St. Paul, MN 55114, and Daniel Steck, Dept. of Physics, St. John's University, Collegeville, MN 56321

ABSTRACT

In regional surveys, indoor radon is usually the parameter of interest, but occasionally soil gas radon at depths of 1 meter or less is also measured. At statewide scales, even limited data sets can be used to infer relationships between geology and soil gas or indoor radon. However, predicting the radon potential of a single house or even an area the size of a neighborhood is more difficult. As the size of a surveyed area decreases, site-specific variables become more significant.

We recently completed a study of two residential neighborhoods within 7 kilometers of each other near Rochester, Minnesota. Eight holes were augered into glacial sediments to maximum depths of 4.5 meters and samples collected for grain-size analysis, measurement of radon parent/daughter nuclides and radon emanation. A total of 65 homes in the areas were provided with two alpha-track registration detectors for 1 year of indoor monitoring.

Positive correlations were observed between the average soil radon, the average indoor radon, and the precursor/daughter radionuclides. The study area with the most topographic relief also had the highest radionuclide contents, the most variability with depth, and some variation with time and soil moisture; these results were not observed at the low-relief site. The type of study described would best be applied to site-specific preconstruction screening, rather than to predicting radon in existing structures.

INTRODUCTION This project was designed to collect data on soil type and soil characteristics, radon and other related nuclides at several depths, and porosity and permeability. At the same time, radon levels in basements and living areas of homes built on the soils were also measured: 1. A.T 1.1 544 F

Two areas were chosen for the pilot study (Figure 1). St. Marys Hills on the west side of Rochester consists of modern, singlefamily homes on 1/2-acre to 2-acre lots on the west side of a bedrock hill composed of St. Peter Sandstone, Decorah Shale, and Galena limestone, with a total vertical relief of about 40 meters. The bedrock surface is covered by 2 and 6 meters of glacial sediment and loess. Essex Park, about 6.5 kilometers northeast of St. Marys Hills is a mix of modern, single-family and multipleresidence homes on 1/2-acre lots. The topography is subdued, with about 9 meters of relief. Depth to the bedrock (Prairie du Chien Group) is between 3 and 18 meters. The profiles for each area and locations of the sample holes are shown in Figure 2.

C 06. Sixty-four owners of single-family homes participated in the . 35 study, 45 from Essex Park and 19 from St. Marys Hills. Each' received two radon detectors; one for the basement and one for a first-floor living area. Exposures lasted from 9 to 12 months.

> 1 ... c,

- # / W 11. \ \ \ \.

METHODOLOGY 2 X X 「「袋」が「小」 21 12. The test holes were drilled in October 1988 using a truckmounted Giddings soil auger with a 5-cm-diameter bit and core tube. Sediment samples collected during drilling were placed in sealable plastic bags.

141.40

1.000

The following is a summary of the analyses and methods used to study the sediment samples. "

ENT NED MAD' 6

i _____

1. Moisture content and bulk density: the wet weights were measured within 2 days after collection. Soils were dried for a minimum of 21 hours at 70°C and reweighed. The results are only approximate, because they do not reflect moisture lost prior to 1. . . measurement:

2. Solid particle density: these measurements were based on a procedure from Luetzelschwab and others (1). These results combined with the wet and dry bulk densities can be used to approximate the pore volume in a sample of soil.

3. Grain-size fractions: the soils were screened into fractions consisting of a bulk sample (undifferentiated as to grain size), ~149 μ (sand and gravel), 149-63 μ (very fine sand), and $-63 \ \mu$ (silt and clay by wet sleving).

4. Mineralogy: the mineralogy was determined by examining the >149 µ grain-size fraction with a binocular microscope.

5. Radon: radon emanation was measured from the bulk soil samples, the $\sim 63 \ \mu$, and the $63-149 \ \mu$ fractions using a charcoal trap system modified from an unpublished report by Dr. J.N.

Andrews, University of Bath, England. Scatter in the bulk fraction is thought to result from inhomogeneous radium in the sediment. The reproducibility of the other duplicate analyses was very good, and replicate analyses of radium standards varied by less than 21191 1. * 108. 2. 2

6. 210Po - 210Pb: Polonium-210 was extracted from the sediment with a leaching technique modified from Eakins and Morrison (2), Blake and Norton (unpub.), and D.R. Engstrom (unpub.). The 210Po was assumed to be in radioactive equilibrium with the 210Pb.

7. Radium and thorium: 1-kilogram sediment splits from each depth were analyzed for 226Ra and 232Th by gamma-ray spectroscopy using a high-resolution germanium detector. The measured activities reflect total radium and thorium in the sediments.

8. Radon concentrations in the soil at multiple depths were measured by (1) pumping air from isolated intervals through a liquid scintillation cocktail (active sampling) and by (2) extended monitoring of isolated intervals with alpha-track detectors (passive sampling). Inflatable rubber packers on the outside of hollow PVC pipe were used to isolate each collection point. Each alpha track detector was wrapped in Saran Wrap® to keep out water vapor but still allow diffusion of radon. Initial data from alpha-track detectors is not included in the tables because of large variance in the calibration constant for the detectors used at that time and our doubts about the integrity of . the original packers. In 1989, a redesigned system for both the active and passive sampling was used with more reliable packers and flexible barriers, which prevented vertical air movement if a packer failed.

G E. SOIL CHARACTERISTICS

1 6 S. S. S. E.

67.5

2.1 The sediments within the Rochester area are the result of glacial processes and include tills, outwash, colluvium, and loess. loess, ranging from 0.6 to 2.8 meters thick, covers all of the sample sites except Hole B in St. Marys Hills. The glacial tills below the loess are oxidized; some show the reddish-brown colors of ferric from to depths of about 4.3 meters (Figure 3),

Moisture ranged from a low of 6.8 weight percent in the loess to a high or 20 weight percent, also in loess. Soil moisture increased slightly with depth, but not in all holes and not more than a few rotcent. Between the initial sampling in 1988 and measurement of radon in 1989, Hole B (St. Marys Hills) collected perchq water in the bottom meter. This could have been due to seepage from the sediment or water infiltrating from the surface.

15.3 There is a fairly broad range of grain-size distributions in 0.124 the rediment damples, but the means within and between the sites were not statistically different. The available data do not allow us to distinguish between the relative effects of deposition and post-depositional soil development on the grain-size distribution.

i tha tha gala in dala 8 814 -2 700 room it indiater. This is an Mineralogically the sediments are very similar, beingpredominantly composed of quartz, feldspar, biotite, and muscovite. Rock fragments form up to 50% of the >149 μ size fraction and include granite, limestone, quartzite, sandstone and metamorphic and volcanic rocks. Varying percentages of magnet te, pyrite, hematite, and limonite were also observed.

RADIOMETRIC RESULTS

· . 2

1. 1.00

Radon concentrations in the soil gas at St. Marys Hills generally increase with depth and range from 17 to 71 kBq/m³ (Table 1), with an average of 44 \pm 13. In Hole A, both active and passive radon samples were collected. Below 1 meter, the two methods gave concentrations that were, within error, identical. The lower radon value at sample point A1 using the active monitor was probably due to leakage around the original packer. A second group of passive monitors was placed in Hole B during August-November and produced results that were significantly lower than the July-August measurements. Hole B also contrasts with the other St. Marys Hills data in that radon decreases with depth. These trends appear related to increased water retention in the clayey soil of Hole B as well as collection of water in the lower meter.

In Essex Park the radon levels range from 3 to 42 kBq/m³ with an average of 26 \pm 7 kBq/m³ (Table 2). The level of 3 kBq/m³ was obtained at a depth of 0.2 meters in Hole G; at a depth of one meter the lowest concentration was 13 kBq/m³. Some of the holes show an increase in radon with depth; others show relatively uniform levels. Some of the radon concentrations measured by the active sampling are as much as 30% lower than concentrations measured with the passive monitors. However, the means? are not statistically different.

A second set of measurements in Hole G during August-November showed lower radon levels than during July-August and correspond to the decrease observed in Hole B at St. Marys Hills. Although the decrease can be attributed to higher water retention in the soil during a rainy fall it is difficult to be sure as only one hole was measured within each area during the late fall.

Radon emanation was measured on the bulk samples, the 63-149 μ and the <63 μ fractions as described above. Replicate analyses gave reproducible results with standard deviations comparable to the error associated with counting statistics. A number of factors, such as moisture, radium content, and location of radium either on grain interiors or secondary coatings, control the amount of radon emanated (3); however, on the average, higher radon emanation would be expected to produce higher radon concentrations in the soil gas. In Tables 3 and 4 the emanation results are given relative to the mass of the sample. The <63- μ fraction includes both silt and clay, and the 63 149 μ (very fine sand) represents about a third of the total sand fraction (up to 2 mm in size). In estimating total emanation, the results from the

63-149 μ measurements were considered representative of all the sand-size fractions. $\hfill \ensuremath{\mathbb{C}}$

.

Differences between the radon emanation rates of the two sites, were comparable with those of the radon concentrations. The average radon emanating from the soils in St. Marys Hills is just over twice that emanating from the Essex Park soils. The difference in means is statistically significant at the 0.025 confidence level. Although emanation rates in St. Marys Hills were divided fairly evenly between the 63-149 μ and <63 μ size fractions, in Essex Park the emanation rates for 9 out of 10 samples was highest in the <63 μ fraction. The variation of emanation rates in St. Marys Hills, in accordance with the more uniform radon concentrations in Essex Park.

The sum of the emanation rates from the grain-size fractions should be comparable with the emanation rate measured from each of the bulk samples. In Essex Park this was the case, but in St. Marys Hills, although most were comparable, some soils, such as A6, had a bulk emanation rate that was larger than either the individual or the sum of the fractional emanations. The overall agreement between the bulk and weighted fractional emanations indicates that the assumption that the 63-149 μ size represents the total sand fraction is reasonable for these samples.

Other radionuclides measured included ²³²Th, ²²⁶Ra, and ²¹⁰Po (Tables 5 and 6). Both the mean and standard deviation of ²³²Th are equivalent for both sites. Radium and ²¹⁰Pb values were higher in St. Marys Hills than in Essex Park and were also more variable both within and between sites than was thorium. If postdepositional migration altered the radionuclide distributions, it did not affect thorium, which is not mobile under near-surface geochemical conditions. Uranium isotopes, however, respond to weathering and changing oxidation/reduction environments; leading to separation from daughter radionuclides and altered distributionpatterns. The relatively uniform distributions of radionuclides in Essex Park sediments are consistent with little post-depositional migration, whereas the uneven distributions in St. Marys Hills for indicate significant migration, possibly related to enhanced weathering ef the sediments on the hill shope as an of 2000 more thank

The activity ratio 210pb/226Ra in the sediment can be a useful to a useful to a useful the sediment can be a useful that radon the radium source, fesulting in the radium source, fesulting in the radium source, fesulting in the set ivity ratios less than unity; in fact the overall activity ratios less than unity; in fact the overall activity ratio is about 0.5, with St. Marys Hills having a somewhat higher mean value (significant at the 0.05 confidence level). Lower activity ratios could also result from only partial recovery of polonium from the sediment, with the apparent effect of reducing the Pb/Ra activity ratio. Sample A6, with an activity ratio of 1.25, is at present an anomaly because the individual

activities of ²¹⁰Pb and ²²⁶Ra, as well as the activity ratio, are much greater than those of the other samples.

Contrary to expectations, the lowest activity ratios were not always near the surface where radon could easily escape into the atmosphere. The sandy soils in Essex Park with the lowest activity ratios imply that radon has moved away from its source even at depths of 3 meters. Disequilibrium between ²²⁶Ra and ²¹⁰Pb could also result from downward migration of radium during weathering of the sediments or could, as noted above, be partially related to inefficient extraction of polonium from the sediment. We were not able to compare the radon directly with either ²²⁶Ra or ²¹⁰Pb because the units were different (volume vs. mass), and the samples did not always correspond in depth.

We also used a 1-inch NaI detector to measure the total gamma activity at 2-foot intervals in several of the holes. In general the activity versus depth relationship followed the pattern of radium and polonium in the sediment except near the surface, where there may have been accumulations of potassium. Total gamma activity in the sediment appeared higher in St. Marys Hills, in accordance with the other measurements, but not all holes were measured. The results do indicate that subsurface gamma activity is a potentially useful and simple screening technique, which could be improved by using a spectroscopy system that determines the energy of the radiation and identifies the isotopes present.

INDOOR RADON

The summary of the indoor radon information is given in Table 7. Of the 64 homeowners who were given the two detectors, 48 returned them. Of those, 17 were from the St. Marys Hills area and 31 from the Essex Park area. The mean indoor radon levels of St. Marys Hills and Essex Park are different and significant at the 0.025 level for a two-sided t-test. The higher average indoor radon in St. Marys Hills corresponds to the higher average radionuclide contents in the sediments of St. Marys Hills and to the higher radon emanation rates. The range of indoor radon concentrations is similar for both areas; each has levels that exceed 370 Bg m⁻³ and levels that are less than 37 Bg m⁻³. Although this reduces the probability of predicting radon levels for individual homes, there is a good correlation between the average soil radon concentrations, parent/daughter radionuclides, and indoor radon levels

indoor radon levels.

Our primary objective in this study was to measure, in two different areas, radionuclides related to and including radon at several depths within unconsolidated sediments, and to see what, if any, correlation existed between the characteristics of the sediment and indoor radon levels. All of the measurements were made in glacially derived or related material. None were obtained

from the limestone bedrock, which was encountered in only three holes. We think that within the study areas the glacial sediments are the primary source of indoor radon and that bedrock probably is not a significant source. A more extensive study is needed to determine which homes were built on or near bedrock and collect additional data on the radon and other radionuclide levels.

Radium-226, ²¹⁰Pb, radon emanation; and downhole radon levels all have statistically higher averages in St. Marys Hills sediments than those in Essex Park. Indoor radon levels also were statistically higher in St. Marys Hills, and had a positive correlation with the radionuclides in the soil. The mineralogy, moisture levels, and bulk densities were similar in both areas and did not correlate with the radionuclide distribution. Texturally the sediments were variable but showed similar average contents of gravel, sand, and silt/clay; however, more work is needed before firm conclusions can be made about the effect of grain-size distribution on the radionuclide content and distribution within the sediments.

All of the techniques used to assess the radon potential were consistent with each other and could be applied individually or collectively to other areas. We believe that at these sites near Rochester mineralogical characteristics of the sediments and the location of samples within the stratigraphic column were only partially responsible for the observed distribution of radionuclides. We suggest that post-depositional transport of uranium and radium related to weathering processes contributed to the observed distributions. The redistribution of radionuclides_ was more extensive in the St. Marys Hills area probably owing to the greater vertical relief. In both areas ²²⁶Ra/²¹⁰Pb activity ratios indicate migration of radon independent of the 10 - 1005° 2001-1117-11 parent/daughter movement. Cr *.

Predicting radon source areas in regions where sediments are more than a couple of meters thick should not be be based solely on identification of geological materials or on near-surface radon measurements: Evidence for the secondary transport and redistribution of radionuclides is not shown on geologic maps, and near-surface radionuclide characteristics may differ from those at basement depth. The data from this study, although limited in area, indicate that measurement of radon or related radioactive nuclides in solito can be a useful preconstruction indicator of potential indoor radon problems. Survey methods could involve active measurements at depths greater than 1 meter of soil gas radon, subsurface gamma spectroscopy and ²²⁶Ra in the sediment.

The work described in this paper was not funded by the U.S. Environmental Protection Agency and therefore the contents do not necessarily reflect the views of the Agency and no official endersement should be inferred.

43

a. 2.3

REFERENCES

2.

1 224 1 1

....

-2

- 1. Luetzelschwab, J.W., Helweick, K.L., and Hurst, K. A. Radon concentrations in five Pennsylvania soils. Health Physics. 56: 181, 1989.
- 2. Eakins, J.D., and Morrison, R.T. A new procedure for the determination of Lead-210 in lake and marine sediments. International Journal of Applied Radiation and Isotopes. 29: 531, 1989.
- 3. Nazaroff, W.W., and Nero, A.V., Jr. Radon and its decay products in indoor air. J. Wiley & Sons, 1988. 518 pp.
- Olsen, B.M. Bedrock geology, Plate 2 of 9. Balaban, N.H., 4. editor. Geologic atlas of Olmsted County, Minnesota Geological Survey County Atlas Series, Atlas C-3, Scale 1:100,000. i. .
- Hobbs, H.C. Surficial geology, Plate 3 of 9. Balaban, N.H., 5. editor. Geologic atlas of Olmsted County, Minnesota Geological Survey County Atlas Series, Atlas C-3, Scale 1:100,000.

Partial funding for this project was provided the the Center for Urban and Regional Affairs, University of Minnesota, Minneapolis:

100

2

1141

6

1.00 არის მერის გარების მორიანი მორირების იმის იყოდოს გრითრიდიელი, იმზები მერის რებლი რებლი არიანი კორი მს T. 101 141

"ide"

1-1-1-1

twine 11 most move and tests of the sone light

£ de.

14

2.2.8

551

0 18

41.00

12 6

48.8 02.0

0118

+ 3

. ê.

-5

- 1. L .

12

20

21

63

2 .5

· 21 1111

10

1.170

1 -

. S.

1-22

19.14

5 24

- E ...

13

Sample No Depth (m)	Date mo/yr	Active (kBq/m ³)	Date mo/yr	Passive (kBq/m ³)	Date mo/yr	Passive (kBq/m ³)
A1-1	10/88	17 ± 2	7-8/89	29 ± 4	-	-
A3-3 A4-4	10/88	40 ± 3 61 ± 4 68 ± 6	7-8/89	40 ± 8 57 ± 8 71 ± 9	nê ji	-
B1-1 B2-2 B3-3 B4-4	-	-	7-8/89 7-8/89 7-8/89 7-8/89	42 ± 6 41 ± 6 29 ± 4 water	8-11/89 8-11/89 8-11/89 8-11/89	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$
C1-1 C2-2	-	1	7-8/89 7-8/89	26 ± 3 44 ± 6	· <u>-</u>	-
D1-1 D2-2 D3-3	-		7-8/89 7-8/89 7-8/89	44 ± 6 46 ± 6 53 ± 7	<u> </u>	-
Average		-	1	44 + 13		

TABLE 1. DOWNHOLE RADON MEASUREMENTS, ACTIVE & PASSIVE - ST. MARYS HILLS

Error values are one standard deviation based on counting statistics.

TABLE 2. DOWNHOLE RADON MEASUREMENTS, ACTIVE & PASSIVE - ESSEX FARK

1 A 13 P

Sample No Depth (m)	Date mo/yr	Active (kBq/m ³)	Date mo/yr	Passive (kBq/m ³)	Date mo/yr	Passive (kBq/m ³)
E1-1 E2-2	8/89	22 ± 2 21 + 2	7-8/89	15 ± 2 22 + 3	-	-
E3-3	8/89	21 ± 2	7-8/89	18 ± 3		_
F1-1	8/89	15 ± 2	7-8/89	21 ± 3	-	-
F2-2	8/89	26 ± 3	7-8/89	32 ± 4	-	-
F3-3	8/89	27 ± 3	7-8/89	24 ± 3	-	-
F4-4	8/89	27 ± 3	7-8/89	36 ± 5	-	-
G1-1 (0.2)*	8/89	3 ± 0.3	7-8/89	18 ± 3	8-11/89	20 ± 1
G2-2 (1.2)*	8/89	23 ± 2	7-8/89	31 ± 4	8-11/89	28 ± 2
G3-3 (2.2)*	8/89	24 ± 2	7-8/89	33 ± 4	8-11/89	23 ± 2
G4-4 (3.2)*	8/89	31 ± 3	7-8/89	42 ± 6	8-11/89	collapsed
H1-1	8/89	13 ± 1	7-8/89	23 ± 3	-	-
H2-2	8/89	21 ± 2	7-8/89	25 ± 4	-	
H3-3	8/89	19 ± 1	7-8/89	25 ± 4	-	-
H4-4	8/89	17 ± 1	7-8/89	23 ± 3	-	-
Average		22 ± 5†		26 ± 7		-

*Depth (meters) of active radon measurements in Hole G. Error values are one standard deviation based on counting statistics.

†Average does not include sample from depth 0.2 meters.

	TABLE 3.	EM	ANATION RESUL	TS	- ST. MARYS	HILLS	32
Sample No. Depth (m)	Bulk Emanation (Bq/kg)	S from	um of Emanation Sand &(Silt+Clay (Bq/kg)	/)*	Emanation 63-149 μ (Bq/kg)	Emanation <63 µ (Bg/kg)	-
A1-1.3 A2-2.1 A3-2.9 A4-3.5 A5-4.0 A6-4 6	7.6 ± 0.4 $\pm 10.6 \pm 0.7$ 20.1 ± 1.0 20.2 ± 0.9 11.0 ± 0.6 $\pm 38.2 \pm 3.3$		14.7 ± 0.7 14.3 ± 0.7 18.0 ± 0.9 22.4 ± 1.1 12.3 ± 0.6 17.5 ± 0.9		$16.7 \pm 0.9 \\ 11.0 \pm 0.8 \\ 15.9 \pm 0.9 \\ 19.1 \pm 1.0 \\ 11.4 \pm 0.7 \\ \pm 13.7 \pm 0.8$	$^{+14.6 \pm 1.0}_{+16.9 \pm 1.0}$ $^{21.3 \pm 0.9}_{26.8 \pm 1.2}$ $^{14.5 \pm 1.0}_{14.5 \pm 1.0}$	
B1-1.9 B2-3.4 B3-4.6	$\begin{array}{c} 15.6 \pm 0.7 \\ 11.1 \pm 0.8 \\ 13.8 \pm 0.7 \end{array}$	4	9.5 ± 1.2 12.2 ± 0.6 11.1 ± 0.6		6.6 ± 0.6 20.2 ± 0.9 †15.0 ± 0.8	†11.2 ± 1.7 11.9 ± 0.6 †10.9 ± 0.6	1
C2-1.8 C2-2.9	18.8 ± 1.0 11.0 ± 0.6		11.4 ± 0.6 12.0 ± 0.6	¢	21.7 ± 1.0 19.5 ± 0.8	11.2 ± 0.6 †11.2 ± 1.7	\$
D1-1.2 D2-2.7	18.2 ± 0.7 34.0 ± 2.0		12.1 ± 0.6 27.1 ± 1.4	5	32.4 ± 2.0 21.8 ± 1.0	11.4 ± 0.7 30.9 ± 1.0	21
Average	17.7 ± 9.2		-		-	-	

*Emanation measured on 63-149 µ size and applied to total sand fraction; emanation from <63 µ size includes both = =. silt and clay. Sum is the measured emanation times the weight percent of each size fraction. †The number is mean of replicate measurements; error is the standard deviation about the average. y?

12

Sample No. Depth (m)	Bulk Emanation (Bq/kg)	Sum of Emanati from Sand &(Silt+C (Bq/kg)	on Clay)*	Emanation 63-149 μ (Bq/kg)	Emanation <63 μ (Bq/kg)	<u></u> 58	
E1-1.9 E2-3.1	†6.3 ± 0.6 8.2 ± 0.5	6.8 ± 0.7 12.3 ± 1.2	(e= 11)	NS‡ 11.4 ± 0.7	- 16.5 ± 1.0 14.9 ± 0.8	1 <u>38</u> 111	
F1-1.8 F2-3.1 F3-4.3	9.8 ± 0.7 11.8 ± 0.6 8.8 ± 0.6	$\begin{array}{c} 12.7 \pm 1.2 \\ 9.3 \pm 0.6 \\ 8.0 \pm 0.8 \end{array}$	*.	35.5 ± 1.4 5.0 ± 1.0 †2.2 ± 0.6	$\begin{array}{c} 10.1 \pm 0.6 \\ 9.4 \pm 1.0 \\ 10.0 \pm 0.7 \end{array}$		
G1-1.9 G2-3.3 G3-4.4	7.4 ± 0.6 7.2 ± 0.5 $\pm 10.5 \pm 0.7$	5.6 ± 0.8 6.3 ± 0.8 6.7 ± 0.8	6 °	3.1 ± 0.4 2.7 ± 0.4 †1.2 ± 0.5	10.6 ± 0.6 9.5 ± 0.7 10.7 ± 0.8	134	
H1-1.8 H2-3.3 H3-4.3	5.6 ± 0.7 4.7 ± 0.8 5.2 ± 0.5	5.6 ± 0.8 5.2 ± 0.8 4.8 ± 0.7	1 -	2.8 ± 0.4 2.3 ± 0.4 2.0 ± 0.4	9.4 ± 0.6 9.7 ± 0.7 f0.0 ± 0.7	5.5 1.F + 4 CE	
Average	7.8 ± 2.3	-		. –	-	<u></u>	

TABLE 4. EMANATION RESULTS - ESSEX PARK

fraction; emanation silt and clay. Sum is the measured emanation times the weight percent of each size fraction. 1 h + --The number is mean of replicate measurements; error is the standard deviation about the average. tNS indicates insufficient sample for measurement. e seal

and a contraction of the and peripheral ends of the present water of an one of the second terms of t

TAB	LE 5. RADIUM-	226, LEAD-210 AND	THORIUM-232 IN	ST. MARYS HILLS	
Sample No. Depth (m)	Ra-226 (Bq/kg)	Pb-210 (Bq/kg)	, Th-232 2 (Bq/kg)	10 _{Pb/226Ra} ±≈10%	i in
A1-1.3	82 ±, 10	†24.9 ± 0.7	32 ± 14	0.30	
A2-2.1	77 ± 10	†18.8 ± 2.6	48 ± 18	0.24	1.5
A3-2.9	74 ± 09	37.8 ± 0.6	29 ± 15	0.51	
A4-3.5	64 ± 09	37.2 ± 0.5	55 ± 19	0.58	
A5-4.0	- 45 ± 07	26.4 ± 0.5	23 ± 17	0:59	
A6-4.6	117 ± 12	+146 ± 46	38 ± 18	1.25	
B1-1.9	30 ± 6	23.7 ± 0.6	33 ± 16	0.79	1
B2-3.4	47 ± 8	26.4 ± 0.5	55 ± 15	0.56	
B3-4.6	$4\dot{2} \pm 7$	27.0 ± 0.7	55 ± 14	0.64	1.1
C1-1.8	60 ± 9	39.9 ± 0.8	45 ± 19	0.67	e
C2-2.9	- 39 ± 7	25.8 ± 0.6	34 ± 16	0.66	
D1-1,2	39 ± 7	32.3 ± 0.7	42 ± 17	0.83	
D2-2.7	79 ± 9	†54.9 ± 7	44 ± 13	0.69	
Average	61 ± 25	40 ± 33	41 ± 11 ***	0.64 ± 0.25	10

†The number is the mean of replicate measurements; error is the standard deviation about the average.

	TABLE	0	KADI	UM-220, L	EAD-210	AND THE	JRIC	-23	2 IN ESSEX PARK	
Sample No. Depth (m)		a-22 lq/kg	26 g)	P (E	b-210 Bq/kg)	TI ز (E	n-23 Bq/kc	2 1)	. 210pb/226Ra ±≈10%	
E1-1.9	27	±	6	16.	1 ± 0.4	29	÷	10	0.60	
E2-3.1	21	±	5	10.	9 ± 0.4	32	÷Ŧ,	11	0.52	1 25
F1-1.8	39	±.	7	19.	4 :± 0.5	49	÷	17	0.50	5
F2-3.1	36	±:	.7	18.	4 ± 0.8	64	法	20	0.51	
F3-4.3	33	-±:	. 7	16.	1 ± 0.7	50	÷.	17	0.49	
G1-1.9	26	±	5	. 13.:	3 ± 0.3	30	:±-	14	0.51 - 6.3	· · · ·
G2-3.3	25	±-,	.7	1 - 14.	4; ± 0.4	. 37	:±	12	0.58′ . * +	
G3-4.4	28	±:	(6	- († 1 1.)	9: <u>+0.2</u>			. 1.3		12.54
H1-1.8-1		tue	-5		8=±=0.4		: : ± 3	15	0.43	
H2-3.3	23	÷.	5,000	6.	5 ± 0.3	an	±.	14.	star :0.28 - 7 stille *.	ie citrer
H3-4.3	25	ta	s6£ er.:	10000 nort899	20±10,4¢	12 ° 11 ° 31	' <u>+</u> ''	10 "	0.37 ⁱ⁰⁹¹ - 3800	111657.0 6/
Average	28	H.	6	14	4 ± 4	38	÷	12	0.47 ± 0.09	·

TABLE 6. RADIUM-226, LEAD-210 AND THORIUM-232 IN ESSEX PARK

'n

†The number is the mean of replicate measurements; error is the standard deviation about the average.

	Ge	ome Mea	etric n	10.8	Arithmetic Mean	Min.	Max.	
St. Marys Hills			54					
Rn Index No.†	180	• +	1.8		220	70	610	
Rn Basement	250	•+	2.1		270	40	1100	
Rn 1 st Floor	130	•+	3.0		160	30	400	
Essex Park				-	1.2.			
Rn Index No.	60	• +	2.5		90	10	390	
Rn Basement	80	* +	2.4		130	15	650	
Rn 1 st Floor	40	• +	2.7		70	10	280	

¥

TABLE 7. SUMMARY OF RADON LEVELS (Bq/m^3) in homes within the study area

†The radon index number is a weighted average of the two radon measurements in the house. The weighting factor for each floor was an estimate of the amount of time an occupant spends on each floor.

64.00

gette.te



Figure 1. Map showing study areas near Rochester, Olmsted County, Minnesota





Figure 2. Profiles and location of sample holes. Modified from Plates 2 and 3, Olmsted County Atlas (4,5):

> Transformer (Construction of Stransformer) 1.4 State (Construction)



Figure 3. Borehole lithology and sample locations based on field identifications.